



**KANOMAX**  
The Ultimate Measurements

# ANEMOMASTER LITE MODEL 6006-DE

Palm-size and feather-weight standard hot-wire anemometer

Anemomaster™ LITE is a compact and lightweight hot-wire anemometer unit. It offers research-grade accuracy at an affordable, industry competitive price. It comes in a dark metallic blue casing with anti-slip gripping.

## Applications

- ◊ HVAC Testing
- ◊ Facility Maintenance
- ◊ Critical Environment Certification
- ◊ IAQ Investigations



## FEATURES AND BENEFITS

- ◊ Lightweight and compact - great for keeping in the tool kit.
- ◊ Research quality at a contractor-friendly price.
- ◊ Extended 2 year warranty.
- ◊ Single switch operation in a comfortable ergonomic design.
- ◊ Includes 4 pcs. AA batteries, carrying case, and NIST Certificate.

FEATURE		VALUE
Air Velocity	Range	2 to 3940 FPM (0.01 to 20.0 m/s)
	Accuracy Resolution	+/- 5.0% of reading or 0.015 m/s whichever is greater 0.01 m/s (0.01 to 9.99 m/s), 0.1 m/s (10.0 to 20.0 m/s)
Temperature	Range	-4 to 158°F (-20 to 70°C)
	Accuracy Resolution	+/- 1.0°F (0.5°C) 1.0°F (0.1°C)
Power Supply		4x AA batteries
Operation Range	Main Unit	41 to 104°F (5 to 40°C) with no visible condensation
	Probe Storage	-4 to 158°F (-20 to 70°C) with no visible condensation 14 to 122°F (-10 to 50°C) with no visible condensation
Weight		0.4 lbs (180 g)
Dimensions	Main Body	2.4 x 4.7 x 1.2 inches (60 x 120 x 34 mm)
	Probe	Probe Length: 8.1 inches (205 mm) Probe Diameter of Tip: 0.24 inches (6.1 mm)
Warranty		2 years

**KANOMAX USA, INC.**  
219 US HWY 206  
ANDOVER, NJ 07821 USA  
TEL: 973-786-6386  
FAX: 973-786-7586  
E-MAIL: SALES@KANOMAX-USA.COM  
URL: WWW.KANOMAX-USA.COM

**DISTRIBUTED BY:**

