



KANOMAX
The Ultimate Measurements

DUCT AIR LEAKAGE TESTER DALT 6900

Automated commercial duct air leakage testing

Kanomax introduces a new Duct Air Leakage Tester (DALT) for commercial duct systems. The instrument provides step-by-step test configuration and automated leakage testing based on the SMACNA HVAC Air Duct Leakage Test Manual. The instrument is designed for easy transport to the job with a small footprint and stair walker dolly.



DUCT LEAKAGE TESTER SPECIFICATIONS

Duct static pressure range	+/- 10 in. w.g. (+/- 2500 Pa)
Volumetric flow range	2 to 377 CFM (4 to 640 m3/h)
Testing surface area (at 4 in.w.g.)	Up to 10500 sq. ft.
Temperature range	-4 to 140 °F (-20 to 60 °C)
Weight	165 lbs. (75kg)

*Specifications are subject to change without notice..

FEATURES AND BENEFITS

- Step-by-step test configuration and automated leakage testing based on the SMACNA Test Manual.
- Automatically calculates leakage percent per AABC standards.
- Capable of both positive and negative duct leakage tests.
- Easy transport to the job with a small footprint.
- Option to connect two DALTs for bigger projects.



KANOMAX USA, INC.
219 US HWY 206, ANDOVER, NJ 07821
USA
TEL: 973-786-6386
FAX: 973-786-7586
E-MAIL: SALES@KANOMAX-USA.COM
URL: WWW.KANOMAX-USA.COM

DISTRIBUTED BY:

